



MODEL: DCC-18/10LT-4T4

COLD WATER PRESSURE WASHER

Electric Powered Specification

Cold WATER

400V – 4kW

186 Bar Pressure

TECHNICAL DATA SHEET

FOR USE IN NON-REGULATED TERRITORIES ASIA MIDDLE EAST AND AFRICA

TECHNICAL INFORMATION

MODEL	
	DCC-18/10LT-4T4
RATINGS	
Max Pressure (psi)	2660psi
Max Pressure (bar)	186bar
Max Flow (gpm)	3.5gpm
Max Flow (lpm)	10.71lpm
Max Temp (water)	50°C
Min Temp (water)	4°C

APPLICATIONS:

COMMERCIAL

+

RESIDENTIAL

USE

POWERED
BY

ELECTRIC MOTOR

380V/50Hz

APPLICATIONS	
Residential Use	Cleaning driveways, patios, decks, and walkways (removing dirt, moss, oil stains)
	Washing cars, motorbikes, bicycles, boats, and caravans
	Cleaning garden tools, fences, outdoor furniture, and BBQ grills
	Cleaning house exteriors, siding, gutters, and roofs
Commercial Use	Cleaning restaurants, hotels, and malls (exteriors, service areas, dumpsters).
	Graffiti removal from walls and public spaces
	Washing buses, trucks, trains, and aircraft.
	Maintaining sports facilities (stadiums, swimming pools, tennis courts)
	Cleaning construction equipment and vehicles

LD

LIGHT DUTY

TECHNICAL INFORMATION

Electric Motor	
Power Rate	4kW
Voltage	380V
Frequency	50Hz
Speed	1450RPM
Certification	Standard, CE As Required
Phase	Three Phase
Optional Accessories	
	Remote Control Total Stop System
	Long Cable and Plug
	Easy Foam Cannon
	Solid Wheel
Controller	
	-
	-
	-

Pump	
Make	Danau
Model	DBC-1514C
Bore (Plunger Dia.) + Stroke	15mm + 14mm
Manifold Material	Brass Forged
Shaft Dia.	Hollow Shaft 24mm/28mm
Max Input Power	7.5kw
Max Input RPM	1750RPM
Ports on Pump	Inlet 3/8", Outlet 1"
Pressure Regulator	Include, Bolt on trap type
Water Inlet Pressure	0-50psi/3.5bar
Max Inlet Water Temp	50°C
Oil Tank Size	550ml (half level of oil gauge)
Frame	
Type	Powder Coated
Colour	Green
Options	10" Pneumatic Wheel

Accessories Included	
	Spray Gun and Lance:
	Professional Triger Gun
	20" Stainless Steel Lance, M22 X 1/4"QD
	Hose:
	ID5/16"(8mm) x 30ft(10m) steel braided hose, 3/8" Quick connect
	Fittings:
	5Tips 1/4"QD Nozzle, 0°, 15°, 25°, 40° And Soap Nozzle
Policies	
Warranty	1 Year Limited Warranty

Fuels & Lubricants (Recommended)	
Gasoline	-
Oils	15W/40
Key Features	
	High Pressure
	Detergent Injection
	Versatile Nozzles
	Cold Water Only
	Portable
Safety Precautions	
	Wearing Appropriate Safety Wear (Eye Protection and Gloves)
Consumables (Service Parts)	
Engine Air Filter	-
Engine Oil Filter	-
Engine Fuel Filter	-
Dimensions & Weights	
Dimensions (mm)	730 x 530 x 500
Weight (Dry)	55 kg
Weight (Wet)	90 kg

PRODUCT VIEWS



TECHNICAL INFORMATION

Cutting Tip	Chiselling Tip	Flushing Tip
		
Removing stains from concrete or other hard surfaces	Stripping paint, removing grease, mildew and stains	Cleaning dirt from siding, sidewalks and outdoor furniture

Washing Tip	Chemical Tip
	
Washing vehicles, windows, aluminium siding and other delicate surfaces	Applying detergent, misting and rinsing

ASSEMBLED & DISTRIBUTED BY:



Vert Energy Africa (Pty) Ltd
28A Cnr. Avalon & Private Roads,
Westlake View Ext 12, Modderfontein,
Johannesburg, Gauteng, South Africa

General Enquiries
+27 (0)11 453 9669
info@vertgroup.co.za
www.vertgroup.co.za

DEALER DETAILS:
