



MODEL: DCC-12/13LT-3S2

COLD WATER PRESSURE WASHER

Electric Powered Specification

COLD WATER

220V – 3kW

125 Bar Pressure

TECHNICAL DATA SHEET

FOR USE IN NON-REGULATED TERRITORIES ASIA MIDDLE EAST AND AFRICA

TECHNICAL INFORMATION

MODEL	
	DCC-12/13LT-3S2
RATINGS	
Max Pressure (psi)	1810psi
Max Pressure (bar)	125bar
Max Flow (gpm)	3.2gpm
Max Flow (lpm)	12.5lpm
Max Temp (water)	50°C
Min Temp (water)	4°C

APPLICATIONS:

COMMERCIAL

+

RESIDENTIAL

USE

POWERED
BY

ELECTRIC MOTOR

220V/50Hz

LD

LIGHT DUTY

APPLICATIONS	
Residential Use	Cleaning driveways, patios, decks, and walkways (removing dirt, moss, oil stains)
	Washing cars, motorbikes, bicycles, boats, and caravans
	Cleaning garden tools, fences, outdoor furniture, and BBQ grills
	Cleaning house exteriors, siding, gutters, and roofs
Commercial Use	Cleaning restaurants, hotels, and malls (exteriors, service areas, dumpsters).
	Graffiti removal from walls and public spaces
	Washing buses, trucks, trains, and aircraft.
	Maintaining sports facilities (stadiums, swimming pools, tennis courts)
	Cleaning construction equipment and vehicles

TECHNICAL INFORMATION

Electric Motor	
Power Rate	3kW
Voltage	220V
Frequency	50Hz
Speed	2880RPM
Certification	Standard, CE As Required
Phase	Single Phase
Optional Accessories	
	Remote Control Total Stop System
	Long Cable and Plug
	Easy Foam Cannon
	Solid Wheel
Controller	
	-
	-
	-

Accessories Included	
	Spray Gun and Lance:
	Professional Trigger Gun
	20" Stainless Steel Lance
	M22x1/4" QD
	Hose:
	ID5/16"(8mm) x 30ft(10m) steel braided hose, 3/8" Quick connect
	Fittings:
	5Tips 1/4"QD Nozzle, 0°, 15°, 25°, 40° And Soap Nozzle
Policies	
Warranty	1 Year Limited Warranty

Pump	
Make	Danau
Model	DBC-14095C
Bore (Plunger Dia.) + Stroke	14mm + 9 mm
Manifold Material	Brass Forged
Shaft Dia.	24mm
Max Input Power	7.0 HP
Max Input RPM	3400
Ports on Pump	Inlet 1/2" Outlet 3/8"
Pressure Regulator	Include, Bolt on trap type
Water Inlet Pressure	3bar / 45psi
Max Inlet Water Temp	50°C
Oil Tank Size	550ml (half level of oil gauge)
Frame	
Type	Powder Coated
Colour	Green
Options	10" Pneumatic Wheel

Fuels & Lubricants (Recommended)	
Gasoline	-
Oils	15W/40
Key Features	
	High Pressure
	Detergent Injection
	Versatile Nozzles
	Cold Water Only
	Portable
Safety Precautions	
	Wearing Appropriate Safety Wear (Eye Protection and Gloves)
Consumables (Service Parts)	
Engine Air Filter	-
Engine Oil Filter	-
Engine Fuel Filter	-
Dimensions & Weights	
Dimensions	730 x 530 x 500
Weight (Dry)	50 kg
Weight (Wet)	72 kg

PRODUCT VIEWS



TECHNICAL INFORMATION

Cutting Tip	Chiselling Tip	Flushing Tip
		
Removing stains from concrete or other hard surfaces	Stripping paint, removing grease, mildew and stains	Cleaning dirt from siding, sidewalks and outdoor furniture

Washing Tip	Chemical Tip
	
Washing vehicles, windows, aluminium siding and other delicate surfaces	Applying detergent, misting and rinsing

ASSEMBLED & DISTRIBUTED BY:



Vert Energy Africa (Pty) Ltd

28A Cnr. Avalon & Private Roads,
Westlake View Ext 12, Modderfontein,
Johannesburg, Gauteng, South Africa

General Enquiries

+27 (0)11 453 9669

info@vertgroup.co.za

www.vertgroup.co.za

DEALER DETAILS:
