



MODEL: DHCC-25/HT

HOT WATER PRESSURE WASHER

Diesel Powered Specification

HOT WATER

10HP – 7.5kW Yanmar Engine

250 Bar Pressure

TECHNICAL DATA SHEET

FOR USE IN NON-REGULATED TERRITORIES ASIA MIDDLE EAST AND AFRICA

TECHNICAL INFORMATION

MODEL

DHCC-25/HT

RATINGS

Max Pressure (psi)	3620psi
Max Pressure (bar)	250bar
Max Flow (gpm)	4gpm
Max Flow (lpm)	15lpm
Max Temp (water)	100°C
Min Temp (water)	5°C

APPLICATIONS:

COMMERCIAL

+

INDUSTRIAL

USE

APPLICATIONS

Industrial Use	
	Heavy machinery cleaning (mining, agriculture, construction)
	Removing rust, paint, and coatings from metal surfaces (surface prep before painting/coating)
	Cleaning tanks, silos, heat exchangers, pipelines, and reactors
	Food processing plants – sanitizing equipment and work areas
	Oil & gas industry – removing grease, mud, and scale from rigs and pipelines
Commercial Use	
	Cleaning restaurants, hotels, and malls (exteriors, service areas, dumpsters).
	Graffiti removal from walls and public spaces
	Washing buses, trucks, trains, and aircraft.
	Maintaining sports facilities (stadiums, swimming pools, tennis courts)
	Cleaning construction equipment and vehicles

YANMAR

DIESEL ENGINE

HD

HEAVY DUTY

TECHNICAL INFORMATION

Engine	
Make	Yanmar
Model	L100 N-DE
Type	4-stroke, vertical-cylinder, air-cooled diesel
Displacement	435 cm ³
Power	7.5kW (10HP) – 3600RPM
Fuel Type	Diesel
Starter	Electric
Compression Ratio	19:1
Consumption	1.4 l/h
Noise	Mechanical
Fuel Tank Size	5.4l
Oil Tank Size	1.6l
Optional Accessories	
	Foam Cannons
	Extension Wands
	Rotary Nozzles

Pump	
Make	Danau
Model	DBC-1510A5
Bore (Plunger Dia.) + Stroke	15mm + 10mm
Manifold Material	Brass Forged
Shaft Dia.	Hollow Shaft 1"-25.4mm
Max Input Power	13HP
Max Input RPM	3400RPM
Ports on Pump	Inlet 3/8", Outlet 1" (On pump side)
Pressure Regulator	Include, Bolt on trap type
Water Inlet Pressure	0-50psi / 3.5bar
Max Inlet Water Temp	50°C
Oil Tank Size	550ml (half level of oil gauge)
Frame	
Type	Powered Coated
Colour	Light Green
Options	10" solid wheels x2 4" swivel castor with brake x1

Accessories Included	
	Spray Gun and Lance:
	Hot Water Trigger Gun
	20" Insulated Lance
	Hose:
	ID5/16"(8mm) x 10m steel braided hose, 3/8" Quick connect
	Fittings:
	5Tips 1/4"QD Nozzle, 0°, 15°, 25°, 40° And Soap Nozzle
Policies	
Warranty	1 Limited Warranty

Fuels & Lubricants (Recommended)	
Diesel	50ppm or better
Oils	15W/40
Key Features	
	High Pressure
	Portable
	Detergent Compatibility
	Versatile
	Commercial Grade
Safety Precautions	
	Wearing Appropriate Safety Wear (Eye Protection and Gloves)
Consumables (Service Parts)	
Engine Air Filter	114210-12590
Engine Oil Filter	114299-35110
Engine Fuel Filter	114250-55122
Dimensions & Weights	
Dimensions (mm)	1000 x 700 x 900
Weight (Dry)	130 kg
Weight (Wet)	150 kg

PRODUCT VIEWS



TECHNICAL INFORMATION

Cutting Tip	Chiselling Tip	Flushing Tip
		
Removing stains from concrete or other hard surfaces	Stripping paint, removing grease, mildew and stains	Cleaning dirt from siding, sidewalks and outdoor furniture

Washing Tip	Chemical Tip
	
Washing vehicles, windows, aluminium siding and other delicate surfaces	Applying detergent, misting and rinsing

ASSEMBLED & DISTRIBUTED BY:



Vert Energy Africa (Pty) Ltd

28A Cnr. Avalon & Private Roads, Westlake
View Ext 12, Modderfontein,
Johannesburg, Gauteng, South Africa

General Enquiries

+27 (0)11 453 9669

info@vertgroup.co.za

www.vertgroup.co.za

DEALER DETAILS