

# PROFESSIONAL HEATING

## EQUIPMENT MANUFACTURER

PRODUCT CATALOG

### ZHEJIANG ZOBO TECHNOLOGY CO.,LTD

ADD: No.16-2,Xita San Road,Chengxi Industry Zone,  
Yongkang,Zhejiang,China,321300

TEL: 0086-579-8902 5299  
FAX: 0086-579-8902 5288

WEB: <http://www.cnzobo.com>  
E-mail: [sales@cnzobo.com](mailto:sales@cnzobo.com)

**zobo**



**zobo**

**YOU  
NEED A  
HEATER**

**YES!**

**ZOBO**





# COMPANY PROFILE



浙江芝博科技有限公司成立于2011年，是中国领先的工业/家用取暖器制造商和供暖方案服务商，专业生产燃油取暖器、电取暖器、燃气取暖器、生物质颗粒取暖器和新能源取暖器等全能源类加热设备。

到目前为止，我们拥有数条先进的自动化生产流水线，年产能1000000台加热器，依靠先进的设备和经验丰富的人才，确保我们生产出具有国际最高标准最可靠的加热器，并且通过 CE、cETLs、RoHS、SAA、SAI、CSA、GS 等产品认证。

芝博始终专注于以最合理的价格为客户提供高质量产品。本着“优良的品质、竞争力的价格、优质的服务”的原则，产品远销美国、加拿大、俄罗斯、英国、德国等欧洲国家并在众多客户中享有高度的信誉。

Zhejiang Zobo Technology Co. Ltd , established in 2011, is a leading manufacturer and supplier of industrial/home heater in China, specializing in Forced-Air heater, Electric Fan Heater, Electric Infrared Heater, Patio Heater and wood pellet heater.

By far, We have several advanced automatic production lines. Besides, advanced equipment, professional and experienced talent and integrating human resources with a whole collection of management, operation and service ensure us to produce the most reliable heater with the highest international standard and quality, certified by CE, cETLs, RoHS, SAA, SAI, CSA, GS, etc. zobo also is approved by ISO9001 and BSCI system.

Zobo always focus on supply grade A product and heater to customer, with most reasonable price. By keeping the principle of "Excellent quality, Competitive price, Superior service", we have enjoyed high integrity among all of our customer including U.S.A., CA., Russia, U.K., Germany, many European countries and middle east countries.

## 企业愿景

成为工业加热器标杆企业  
成为一家伟大的公司

## VIRSON

Become a leader for industrial heaters and become a great company

## 企业使命

帮助更多的人实现梦想和体现价值

## MISSION

let more people come true and embody value

## 核心价值观

团队合作、敬业、诚信、积极、感恩

## CORE VALUES

Teamwork, Honesty, Dedicated, Energetic, Thankful.



**07-14**

## **KEROSENE/DIESEL AIR HEATER**

---

plus-k series	09-10
K series	11-13
H series	14

**15-24**

## **ELECTRIC FAN HEATER**

---

ET series	17-18
EC series	19-20
EF series	21-22
EY series	23-24

**25-31**

## **GAS AIR HEATER**

---

G series	27
GT series	28
GW series	29
GA series	30
C series	31

**32-34**

## **GAS CAMPING HEATER**

---

TT series	32
GB series	34

# **CONTENTS**

# KEROSENE DIESEL HEATER

## SERIES

**zobo**



AGRICULTURE | AUTOMOTIVE | BUILDINGS AND COMMERCIAL SPACES  
CONSTRUCTION | GENERAL INDUSTRY AND PRODUCTION | MILITARY AND AEROSPACE  
RENTAL COMPANIES

# KEROSENE/DIESEL HEATER

## PLUS-K SERIES

- High air flow
- Two oil filters – oil tank filter and suction filter
- Thermally protected motor
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Trolley included for K105,K135,K180,K220
- Oil tank with level indicator
- Designed for easy handling and transportation
- Easy maintenance



# KEROSENE/DIESEL HEATER

## PLUS-K SERIES

- High air flow
- Two oil filters – oil tank filter and suction filter
- Thermally protected motor
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Trolley included for K105,K135,K180,K220
- Oil tank with level indicator
- Designed for easy handling and transportation
- Easy maintenance



### PLUS K50

### PLUS K80

### PLUS K105

	PLUS K50	PLUS K80	PLUS K105
Voltage	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ
Heat output	13KW	20KW	30KW
Fuel	Kerosene,Diesel	Kerosene,Diesel	Kerosene,Diesel
Fuel Tank	19L	19L	38L
Fuel consumption	1.4L/h	1.9L/h	2.9L/h
Heating Area	300m <sup>3</sup>	400m <sup>3</sup>	600m <sup>3</sup>
Product Size	785*295*445mm	785*295*445mm	990*495*735mm
Net/Gross Weight	14.1/15.2kgs	14.2/15.2kgs	22/24.8kgs
Packing Size	815*345*485mm	815*345*485mm	920*430*535mm
Loading Quantity (20/40/40HQ)	206/392/510 pcs	206/392/510 pcs	125/254/317 pcs
Ignition type	Continuous spark Ignition	Continuous spark Ignition	Continuous spark Ignition
Thermostat control	without	with	with

### PLUS K135

### PLUS K180

### PLUS K220

	PLUS K135	PLUS K180	PLUS K220
Voltage	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ
Heat output	37KW	51KW	63KW
Fuel	Kerosene,Diesel	Kerosene,Diesel	Kerosene,Diesel
Fuel Tank	38L	50L	50L
Fuel consumption	3.8L/h	4.8L/h	5.8L/h
Heating Area	800m <sup>3</sup>	1060m <sup>3</sup>	1300m <sup>3</sup>
Product Size	990*495*735mm	1130*560*735mm	1130*560*735mm
Net/Gross Weight	22.2/25.1kgs	25.6/28kgs	26.21/29.36kgs
Packing Size	920*430*535mm	1075*480*545mm	1075*480*545mm
Loading Quantity (20/40/40HQ)	125/254/317 pcs	100/200/234 pcs	100/200/234 pcs
Ignition type	Continuous spark Ignition	Continuous spark Ignition	Continuous spark Ignition
Thermostat control	with	with	with

# KEROSENE/DIESEL HEATER

## K SERIES

- High air flow
- Two oil filters – oil tank filter and suction filter
- Thermally protected motor
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Trolley included for K100, K125, K175, K215
- Oil tank with level indicator
- Designed for easy handling and transportation
- Easy maintenance



# KEROSENE/DIESEL HEATER

## K SERIES

- High air flow
- Two oil filters – oil tank filter and suction filter
- Thermally protected motor
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Trolley included for K100, K125, K175, K215
- Oil tank with level indicator
- Designed for easy handling and transportation
- Easy maintenance



### ZB K45

### ZB K70

### ZB K100

Voltage	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ
Heat output	13KW(45,000btu)	20KW(70,000btu)	30KW(100,000btu)
Fuel	Kerosene,Diesel	Kerosene,Diesel	Kerosene,Diesel
Fuel Tank	19L	19L	38L
Fuel consumption	1.3L/h	1.9L/h	2.9L/h
Heating Area	260m <sup>3</sup>	400m <sup>3</sup>	600m <sup>3</sup>
Product Size	770*290*395mm	770*290*395mm	880*490*580mm
Net/Gross Weight	12.7/14.0kgs	12.9/14.5kgs	20.0/23.1kgs
Packing Size	805*335*445mm	805*335*445mm	915*445*490mm
Loading Quantity (20/40/40HQ)	245/502/600 pcs	245/502/600 pcs	128/260/325 pcs
Ignition type	Continuous spark Ignition	Continuous spark Ignition	Continuous spark Ignition
Thermostat control	without	with	with

### ZB K125

### ZB K175

### ZB K215

Voltage	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ
Heat output	37KW(125,000btu)	51KW(175,000btu)	63KW(215,000btu)
Fuel	Kerosene,Diesel	Kerosene,Diesel	Kerosene,Diesel
Fuel Tank	38L	50L	50L
Fuel consumption	3.6L/h	4.8L/h	5.8L/h
Heating Area	740m <sup>3</sup>	1020m <sup>3</sup>	1260m <sup>3</sup>
Product Size	880*490*580mm	1060*540*575mm	1060*540*575mm
Net/Gross Weight	20.5/23.5kgs	22.3/25.8kgs	22.8/26.3kgs
Packing Size	915*445*490mm	1065*455*500mm	1065*455*500mm
Loading Quantity (20/40/40HQ)	128/260/325 pcs	108/220/275 pcs	108/220/275 pcs
Ignition type	Continuous spark Ignition	Continuous spark Ignition	Continuous spark Ignition
Thermostat control	with	with	with

# KEROSENE/DIESEL HEATER

## K SERIES-GEAR PUMP

- Overheat thermostat
- Post ventilation
- Thermally protected motor
- Transparent external suction filter
- Three oil filters – oil pump filter, suction filter and inlet filter
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Oil tank with level indicator
- Trolley included
- Easy maintenance with external pump



### ZB K240

### ZB K350

Voltage	220V/50HZ	220V/50HZ
Heat output	70KW	100KW
Fuel	Kerosene,Diesel	Kerosene,Diesel
Fuel Tank	50L	70L
Fuel consumption	6.9L/h	9.8L/h
Heating Area	1400m <sup>3</sup>	2000m <sup>3</sup>
Product Size	1230*550*740mm	1310*500*750mm
Net/Gross Weight	37/42kgs	52/56.5kgs
Packing Size	1215*465*555mm	1295*470*690mm
Loading Quantity (20/40/40HQ)	90/182/210 pcs	67/138/162 pcs
Ignition type	Continuous spark Ignition	Continuous spark Ignition
Thermostat control	with	with

# KEROSENE/DIESEL HEATER

## H SERIES

- Clean hot air
- Optional connection to a flexible tube
- Flue gas exhaust
- Heat exchanger
- Overheat thermostat
- Post-ventilation
- Thermally protected motor
- Two oil filters – oil tank filter and suction filter
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Oil tank with level indicator
- Trolley included




### ZB H70

### ZB H100

### ZB H170

Voltage	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ	110V/60HZ,220V/50HZ
Heat output	20KW(70000btu)	30KW(100000btu)	50KW(170000btu)
Fuel	Kerosene,Diesel	Kerosene,Diesel	Kerosene,Diesel
Fuel Tank	38L	50L	50L
Fuel consumption	1.9L/h	2.9L/h	4.6L/h
Heating Area	320m <sup>3</sup>	480m <sup>3</sup>	800m <sup>3</sup>
Product Size	950*500*600mm	1100*550*600mm	1230*600*710mm
Net/Gross Weight	24.0/26.8kgs	30.5/33.6kgs	38.2/42.7kgs
Packing Size	915*445*490mm	1065*455*500mm	1215*465*555mm
Loading Quantity (20/40/40HQ)	128/260/325 pcs	108/220/275 pcs	80/168/195 pcs
Ignition type	Continuous spark Ignition	Continuous spark Ignition	Continuous spark Ignition
Thermostat control	with	with	with

# ELECTRIC FAN HEATER SERIES



OFFICE HEATING | HOME ENTERTAINMENT AND HEATING  
WORKSHOP HEATING | RESTAURANT HEATING

**WARM WINTER  
BREEZE  
HARVEST A  
HAPPY SMILE**



# ELECTRIC FAN HEATER



## ZOBO ET SERIES

- Stepless temperature adjustment, just as few degrees as you want, adjust at will
- 3 levels of power adjustable, cold/small/large, can not only blow warm air but also natural wind, available in all seasons
- The pitch of the air outlet is adjustable at 90°, and the warm wind blows wherever you want
- PTC ceramic heating element, can meet the use of 10-30M<sup>2</sup> space
- Safety guard, well-designed, using overheat protection, metal air outlet, the body is made of metal and flame-retardant plastic
- The characteristic tripod is reinforced and more stable, and the creative design is full of industrial style.



**ZB ET2C**

**ZB ET3C**

Voltage	220V/50HZ	220V/50HZ
Heating output	20/1000/2000W	23/1500/3000W
Air flow	250m <sup>3</sup> /h	365m <sup>3</sup> /h
Heating Area	40m <sup>2</sup>	60m <sup>2</sup>
Noise	45(dB)	45(dB)
Heating Element	PTC	PTC
Product Size	218*140*250mm	275*175*318mm
Net/Gross Weight	1.5/1.7 kg	2.3/2.8 kg
Packing Size	235*155*260mm	300*205*340mm
Loading Quantity (20/40/40HQ)	3000/5800/7200pcs	1350/2600/3250pcs

# ELECTRIC FAN HEATER

## EC SERIES



- Super calories, instantly enjoy
- High power to meet the heating and drying needs of large spaces
- Gear temperature adjustment, turn on on demand, energy saving and power saving
- Turbine circulation, strong wind, longer air supply distance
- Stainless steel finned electric heating tube, explosion-proof and rust-proof, durable
- Automatically cut off the power when overheated, prolonging the service life of the equipment
- Insulation and anti-scalding metal shell, safer to use



### ZB EC2

### ZB EC3

### ZB EC5T

Voltage	220V/50HZ	220V/50HZ	220V/50HZ
Heating output	20/2000W	25/1500/3000W	29/2500/5000W
Air flow	250m <sup>3</sup> /h	365m <sup>3</sup> /h	320m <sup>3</sup> /h
Heating Area	40m <sup>3</sup>	60m <sup>3</sup>	100m <sup>3</sup>
Noise	62(dB)	45(dB)	48(dB)
Heating Element	Finned Stainless	Finned Stainless	Finned Stainless
Product Size	211*250*326mm	250*290*326mm	360*319*445mm
Net/Gross Weight	3.2/3.7kg	4.0/4.6kg	6.5/ 7.2kg
Packing Size	260*260*340mm	290*300*340mm	320*325*410mm
Loading Quantity (20/40/40HQ)	1200/2300/2950pcs	950/1800/2300pcs	650/1300/1650pcs

# ELECTRIC FAN HEATER

## EC SERIES



- Industrial-grade design, sturdy and durable structure
- Finned heating tube, high heating efficiency
- Built-in thermostat, safer to use
- Reinforced push rod, more convenient and firm to move
- Mechanical knob temperature adjustment
- Whirlpool air duct, strong wind, Longer air supply distance



### ZB EC5

### ZB EC9

### ZB EC15

Voltage	380V/50HZ	380V/50HZ	380V/50HZ
Heating output	31/2500/5000W	70/4500/9000W	85/7000/15kW
Air flow	320m <sup>3</sup> /h	410m <sup>3</sup> /h	1292m <sup>3</sup> /h
Heating Area	100m <sup>3</sup>	180m <sup>3</sup>	300m <sup>3</sup>
Noise	48(dB)	53(dB)	61(dB)
Heating Element	Finned Stainless	Finned Stainless	Finned Stainless
Product Size	360*319*445mm	360*319*445mm	645*484*697mm
Net/Gross Weight	9/ 9.8kg	9.7/ 10.5kg	20.1/21.5kg
Packing Size	400*335*420mm	400*335*420mm	620*410*510mm
Loading Quantity (20/40/40HQ)	500/1000/1200pcs	500/1000/1200pcs	210/420/520pcs

# ELECTRIC FAN HEATER

## EF SERIES



- Smokeless, tasteless, no oxygen consumption, suitable for multi-scene heating
- Three levels of temperature adjustment, turn on on demand, energy saving and power saving
- Quick heat at boot, big heat for small body
- Automatic power off when overheating, safer and more reliable
- Insulated anti-scalding metal shell
- The angle of the air outlet can be adjusted from 15 to 25 ° up and down
- Heat insulation handle, front and rear protective net cover
- Special natural windshield, natural wind in summer



**ZB EF2**

**ZB EF3**

Voltage	220V/50HZ	220V/50HZ
Heating output	25/1000/2000W	29/1500/3000W
Air flow	120m <sup>3</sup> /h	280m <sup>3</sup> /h
Heating Area	40m <sup>3</sup>	60m <sup>3</sup>
Noise	49(dB)	46(dB)
Heating Element	Stainless steel	Stainless steel
Product Size	220*200*320mm	290*253*403mm
Net/Gross Weight	3.5/4.0kgs	5.0/5.7kgs
Packing Size	263*249*350mm	301*299*435mm
Loading Quantity (20/40/40HQ)	1300/2400/2960pcs	720/1350/1750pcs

# ELECTRIC FAN HEATER

## EF SERIES



- Smokeless, tasteless, no oxygen consumption, suitable for multi-scene heating
- Three levels of temperature adjustment, turn on on demand, energy saving and power saving
- Quick heat at boot, big heat for small body
- Automatic power off when overheating, safer and more reliable
- Insulated anti-scalding metal shell
- The angle of the air outlet can be adjusted from 15 to 25 ° up and down
- Heat insulation handle, front and rear protective net cover
- Special natural windshield, natural wind in summer



**ZB EF5**

**ZB EF9**

**ZB EF15**

Voltage	380V/50HZ	380V/50HZ	380V/50HZ
Heating output	31/2500/5000W	51/4500/9000W	90W/5kW/10kW/15kW
Air flow	320m <sup>3</sup> /h	410m <sup>3</sup> /h	1292m <sup>3</sup> /h
Heating Area	100m <sup>3</sup>	180m <sup>3</sup>	300m <sup>3</sup>
Noise	49(dB)	57(dB)	61(dB)
Heating Element	Stainless steel	Stainless steel	Stainless steel
Product Size	290*253*403mm	325*305*443mm	409*343*563mm
Net/Gross Weight	6.4/7.2kgs	9.4/10.4kgs	15/16.5kgs
Packing Size	352*299*435mm	385*370*485mm	425*370*580mm
Loading Quantity (20/40/40HQ)	620/1200/1485pcs	405/810/984pcs	312/625/758pcs

# ELECTRIC FAN HEATER

## EY SERIES



- Smokeless, tasteless, no oxygen consumption, suitable for multi-scene heating
- Three levels of temperature adjustment, turn on on demand, energy saving and power saving
- Quick heat at boot, big heat for small body
- Automatic power off when overheating, safer and more reliable
- Insulated anti-scalding metal shell
- The angle of the air outlet can be adjusted from 15° to 25° up and down
- Heat insulation handle, front and rear protective net cover
- Special natural windshield, natural wind in summer



Optional: 380V industrial plug

### ZB EY3

### ZB EY5

Voltage	220V/50HZ	380V/50HZ
Heating output	29/1500/3000W	31/2500/5000W
Air flow	280m <sup>3</sup> /h	320m <sup>3</sup> /h
Heating Area	60m <sup>3</sup>	100m <sup>3</sup>
Noise	51(dB)	58(dB)
Heating Element	Stainless steel	Stainless steel
Product Size	340*310*410mm	340*310*410mm
Net/Gross Weight	6.2/7.1KGs	7.3/8.1KGs
Packing Size	381*340*425mm	381*340*425mm
Loading Quantity (20/40/40HQ)	520/1000/1230pcs	520/1000/1230pcs

# ELECTRIC FAN HEATER

## EY SERIES



- Smokeless, odorless, no oxygen consumption, suitable for multi-scene heating
- High power and super heat, enjoy it in a moment
- Push frame design, mobile more portable
- Automatic power off when overheating, safer and more reliable
- Insulated anti-scalding metal shell
- The angle of the air outlet can be adjusted from 15° to 25° up and down
- Heat insulation handle, front and rear protective net cover
- Special natural windshield for natural wind in summer



### ZB EY9

### ZB EY15

Voltage	380V/50HZ	380V/50HZ
Heating output	51/4500/9000W	90W/5kW/10kW/15kW
Air flow	410m <sup>3</sup> /h	1292m <sup>3</sup> /h
Heating Area	180m <sup>3</sup>	300m <sup>3</sup>
Noise	53(dB)	61(dB)
Heating Element	Stainless steel	Stainless steel
Product Size	430*410*520mm	490*490*860mm
Net/Gross Weight	11.4/12.2kgs	21.6/22.5kgs
Packing Size	426*411*515mm	475*450*560mm
Loading Quantity (20/40/40HQ)	310/600/755pcs	230/450/568pcs

# GAS AIR HEATER

## SERIES



POULTRY HATCHING FOR HEATING | FARM HEATING  
PARKING LOT HEATING | WORKSHOP DRYING

# GAS AIR HEATER

## G SERIES



- Manual ignition
- Electrovalve
- Safety gas valve with thermocouple
- Regulator and gas hose included
- Motor with thermal protection
- Overheat thermostat
- Easy maintenance



ZB G10

ZB G15

ZB G35

ZB G50

	ZB G10	ZB G15	ZB G35	ZB G50
Fuel type	LPG/Propane	LPG/Propane	LPG/Propane	LPG/Propane
Power supply	220V/50HZ	220V/50HZ	220V/50HZ	220V/50HZ
Heat output	10KW	15KW	30KW	50KW
Gas consumption	0.71Kg/h	1.07Kg/h	2.13Kg/h	3.57Kg/h
Air flow	300m <sup>3</sup> /h	300m <sup>3</sup> /h	750m <sup>3</sup> /h	800m <sup>3</sup> /h
Regulator pressure output	300mbar	300mbar	700mbar	1500mbar
Product size	332*220*310mm	375*220*310mm	475*225*350mm	580*225*355mm
Carton size	380*265*385mm	430*265*385mm	530x280x390mm	630x280x390mm
N.W/G.W	4.18/5.29kgs	4.45/5.39kgs	6.54/7.6kgs	7.35/8.50kgs
Container Qty(20/40/40HQ)	750/1418/1755pcs	660/1250/1550pcs	490/950/1150pcs	400/800/980pcs

# GAS AIR HEATER

## GT SERIES



- Adjustable heat
- Manual ignition
- Double electrovalve
- Safety gas valve with thermocouple
- Regulator and gas hose included
- Motor with thermal protection
- Overheat thermostat
- Easy maintenance



ZB G15T

ZB G35T

ZB G50T

	ZB G15T	ZB G35T	ZB G50T
Fuel type	LPG/Propane	LPG/Propane	LPG/Propane
Power supply	220V/50HZ	220V/50HZ	220V/50HZ
Variable Heat output	7-15KW (adjustable)	12KW-30KW (adjustable)	17KW-50KW (adjustable)
Gas consumption	0.5-1.08Kg/h	0.86-2.16Kg/h	1.22-3.6Kg/h
Air flow	140-300m <sup>3</sup> /h	440-600m <sup>3</sup> /h	900-1000m <sup>3</sup> /h
Regulator pressure output	300mbar	700mbar	1500mbar
Product size	430*225*343mm	480*225*343mm	580*225*343mm
Carton size	480x280x390mm	530x280x390mm	630x280x390mm
N.W/G.W	5.6/6.3kgs	5.9/6.8kgs	6.6/7.5kgs
Container Qty(20/40/40HQ)	540/1070/1250pcs	490/950/1150pcs	400/800/980pcs

# GAS AIR HEATER

## GW SERIES



- Electronic ignition
- Thermostat control
- Double electrovalve
- The ionization electrode continuously checks the presence of the flame
- Regulator and gas hose included
- Motor with thermal protection
- Overheat thermostat
- Adjustable heat
- Strong and long lasting construction
- Easy maintenance



ZB G15W

ZB G35W

ZB G55W

	ZB G15W	ZB G35W	ZB G55W
Fuel type	LPG/Propane	LPG/Propane	LPG/Propane
Power supply	220V/50HZ	220V/50HZ	220V/50HZ
Variable Heat output	7-15KW	15-35KW	18-55KW
Gas consumption	0.5-1.08Kg/h	1.08-2.52Kg/h	1.29-3.96Kg/h
Air flow	300m <sup>3</sup> /h	750m <sup>3</sup> /h	750m <sup>3</sup> /h
Regulator pressure output	700mbar	1500mbar	1500mbar
Product size	484*223*348mm	730*410*655mm	792*410*650mm
Carton size	540*280*400mm	630*370*480mm	690*370*480mm
N.W/G.W	6.7/8.2Kgs	12.5/14.5Kgs	13.2/15Kgs
Container Qty(20/40/40HQ)	470/900/1125pcs	240/465/585pcs	220/420/530pcs

# GAS AIR HEATER

## GA SERIES



- Manual ignition
- Electrovalve
- Safety gas valve with thermocouple
- Regulator and gas hose included
- Motor with thermal protection
- Overheat thermostat
- Easy maintenance



ZB G40A

ZB G60A

ZB G100A

ZB G125A

ZB G150A

	ZB G40A	ZB G60A	ZB G100A	ZB G125A	ZB G150A
Fuel type	LPG/Propane	LPG/Propane	LPG/Propane	LPG/Propane	LPG/Propane
Power supply	110V/60HZ	110V/60HZ	110V/60HZ	110V/60HZ	110V/60HZ
Heat output	40000btu	40000-60000btu	70000-100000btu	95000-125000btu	120000-150000btu
Heating area	234m <sup>3</sup>	234-352m <sup>3</sup>	410-586m <sup>3</sup>	586-740m <sup>3</sup>	704-880m <sup>3</sup>
Gas consumption	0.83kg/h	0.83-1.25kg/h	1.46-2.08kg/h	2.08-2.61kg/h	2.5-3.13kg/h
Air flow	500m <sup>3</sup> /h	500m <sup>3</sup> /h	670m <sup>3</sup> /h	670m <sup>3</sup> /h	670m <sup>3</sup> /h
Regulator pressure output	11.0" w.c	11.0" w.c	11.0" w.c	11.0" w.c	11.0" w.c
Ignition type	Electronic	Electronic	Electronic	Electronic	Electronic
Product size	486*198*335mm	486*198*335mm	655*230*460mm	655*230*460mm	655*230*460mm
Carton size	530x245x370mm	530x245x370mm	695x285x450mm	695x285x450mm	695x285x450mm
N.W/G.W(lbs)	5.6KGS/6.6KGS	5.6KGS/6.6KGS	8.3KGS/10.1KGS	8.3KGS/10.1KGS	8.3KGS/10.1KGS
Container Qty(20/40/40HQ)	570/1180/1440 PCS	570/1180/1440 PCS	300/600/740PCS	300/600/740PCS	300/600/740PCS

# GAS CONVECTION HEATER

## C SERIES

- Continuous Variable BTU Output
- Auto Safety Shutoff
- Inner Windshield
- Aluminized Steel Construction
- Easy maintenance



ZB C80

ZB C200

	LPG/Propane	LPG/Propane
Fuel type	LPG/Propane	LPG/Propane
Heat output	50,000-80,000 BTU	50,000-200,000 BTU
Manifold pressure	11" W.C.	10 PSI
Heating area	120-190m <sup>2</sup>	120-460m <sup>2</sup>
Net/Gross Weight	3.9/5.2kgs	4.8/6.5kgs
Packing Size	430x430x330mm	430x430x410mm
Loading Quantity (20/40/40HQ)	450/950/1100pcs	360/760/890pcs

# TANK TOP HEATER

## TT SERIES



- Quiet operation
- Quick Connect P.O.L Tank Connection
- For indoor or outdoor use
- Safety Shut-Off Valve
- With Anti-tip device
- CSA Approved



\*The propane cylinder is separately.

ZB TT15

ZB TT30

ZB TT360

	LPG/Propane	LPG/Propane	LPG/Propane
Fuel type	LPG/Propane	LPG/Propane	LPG/Propane
Tank capacity	20Lb	20Lb	20Lb
Variable heat output	9k-13k-15k BTUs	18k-26k-30k BTUs	30k-35k-42k BTUs
Heating area	378sq.ft	750sq.ft	1010sq.ft
Product size	210*170*320mm	440*170*315mm	230*230*550mm
Packing size	240*210*325mm	450*175*322mm	455*245*260mm
N.W/G.W	1.1/1.47kgs	2.18/2.63kgs	1.95/2.6kgs
Container Qty(20/40/40HQ)	1750/3600/4200pcs	1100/2300/2700pcs	900/1900/2200pcs

# HEATER & COOKER

INNOVATIVE • PORTABLE • SAFETY



# GAS HEATER

## GB SERIES



- Dura-USE design(Patent): Heating and Cooking
- Accidental tip-over safety shut-off
- Automatic low oxygen shut-off system (ODS)
- Quiet, clean, odor-free operation
- Heavy-duty design



ZB GB4

ZB GB9

ZB GB18

	ZB GB4	ZB GB9	ZB GB18
Fuel type	Propane	Propane	Propane
Tank Capacity (Min)	1 lb Propane Cylinder	1 lb Propane Cylinder	2*1 lb Propane Cylinder
Variable heat output	4000 BTUs	4000-9000 BTUs	4000-9000-18000 BTUs
Fuel Consumption/Burn Rate (Gal/Hr)	0.044 Gal/hr	0.044-0.099 Gal/hr	0.044-0.198 Gal/hr
Heat Area	95 Sq.ft	225 Sq.ft	450 Sq.ft
Ignition type	Piezo	Piezo	Piezo
Safety Tip-Over Switch	No	YES	YES
Oxygen Depletion Sensor (ODS)	YES	YES	YES
Net Weight	6 lbs	11 lbs	18 lbs
Product size	10.5*8.5*17 inch	13.0*8.5*13.0 inch	17.5*11*17.0 inch